

**Firebox Black
(843N3619)**

Firebox Black is a modified resin blended to provide special heat resistant qualities that makes this a very unique product. Unlike many hi heat coatings, **Firebox Black** is economical as well as a superb coating used for many applications where heat resistance is a must.

Firebox Black, designed for various uses:

- **Bar-B-Que Grills**
- **Fireplace Tools**
- **and many others**

Ordering:

Available in single gallons.

Technical Data

Type: Silicone

Components: One

Colors: Black (843N3619)

Gloss: Flat

V.O.C. 5.76 lbs. per gallon

Solids by Volume: 26% + or - 2%

Flash Point: 50° F.

Shelf Life: 1 year

Temperature Resistance: 850° F.

Surface Preparation: Remove all contaminants including oil, grease, loose paint, dirt or any other contaminants. Recommended removal is SSPC-SP3 Power Tool Cleaning.

Mixing: Stir thoroughly prior to use.

Recommended Film Thickness: 1.5 - 2.0 mils dry film.

Spreading Rate: 640 sq. ft per gal. @ 1 mil
320 - 425 sq. ft. per gal. @ recommended dft.

Pot Life: N/A

Dry Time: @ 77° F.

To Touch: 20 minutes

Tack Free: 40 minutes

Dry Hard: 24 hours

Application: Brush, roll, or spray.

Thinning: Needed for spray application only; as necessary up to 10% with XL Thinner.

Clean-up: XL Thinner

Note: For Shop Application only.

05/07