

**SC 1140 Snap Dry Aluminum  
(888S2208)**

**SC 1140 Snap Dry Aluminum Paint** is a quick drying bright aluminum finish that was formulated to have good reflective and weathering properties for exterior exposure.

**SC 1140** is a very economical aluminum paint that is ideal for coating small propane cylinders, racks, railings and many other items.

**Technical Data**

**Type:** Aromatic Hydrocarbon

**Components:** One

**Colors:** Aluminum

**Gloss:** n/a

**V.O.C:** max. 4.2 lb/gal or 503 gr/lit  
Theoretical unreduced 4.0 lb/gal.

**Solids by Volume:** 41.19 +/- 2%

**Flash Point:** 45° F.

**Shelf Life:** 1 year

**Temperature Resistance:**  
Up to 200° F. Intermittently

**Surface Preparation:** Remove all contaminants including oil, grease, loose paint, dirt or any other contaminants. This product performs well over surfaces cleaned according to SSPC-SP-3 Power Tool Cleaning. Minimum of SSPC-SP, Hand Tool Cleaning required.

**Application:** Brush, roll, or spray. Spraying provides better finish.

**SC1140 Offers:**

- Brilliant Finish
- Weather Resistance
- Corrosion Protection
- Lead and Chrome Free
- Fast Dry

**Ordering:** Available in single gallons.

**Recommended Primer:** Uni-Pox Primer – 855W1370 (Off White) or 855G1368 (Gray-Green).

**Mixing:** Stir thoroughly prior use.

**Recommended Film Thickness:** 1.5 - 2.0 mils dry film.

**Spreading Rate:** 628.2 sq. ft per gal. @ 1 mil.  
330 - 440 sq. ft. per gal. @ recommended dft.

**Pot Life:** N/A

**Dry Time:**  
To Touch: 15 min.  
Tack Free: 30 min.  
Re-coat: 45 min.

**Thinning:** No thinning required.

**Clean-up:** XL Thinner (856X2210), Xylene or Mineral Spirits.

**Special Note:** Product is water and moisture sensitive.