

**SC2000 Aluminum Tank Paint
(888S2005)**

SC2000 Aluminum Tank Paint is a premium resin blend that was formulated with a maximum amount of aluminum to give years of service. SC2000 provides an excellent finish for bulk storage tanks, customer tanks, pipes, and many other uses.

Ordering: Available in single gallons and five gallon pails

Technical Data

Type: Modified Oils

Components: One

Colors: Aluminum

Gloss: High

V.O.C.: max. 3.9 lbs/ gal. or 468 gr/lit
Theoretical unreduced 3.71 lbs/gal

Solids by Volume: 44% ± 2%

Flash Point: In excess of 80° F.

Shelf Life: 1 year

Temperature Resistance:
Up to 350° F. Continuously

Surface Preparation: Remove all contaminants including oil, grease, loose paint, mill scale, dirt or any other contaminants. SSPC-SP-3 Power Tool Cleaning recommended.

Application: Brush, roll, or spray.

SC2000 Features:

- Long Life
- Bright Finish
- Lead & Chrome Free
- Excellent Weather Durability
- Maximum Amount of Aluminum in Every Gallon

Recommended Primer:

Uni-Pox Primer-
855W1370 (Off White)
855G1368 (Gray-Green)

Mixing: Stir thoroughly prior use.

Recommended Film Thickness: 1.5 - 2.0 mils
dry film.

Spreading Rate: 710 sq. ft per gal. @ 1 mil.
365 - 455 sq. ft. per gal. @ recommended dft.

Pot Life: N/A

Dry Time:
To Touch: 11/2 - 2 hours
Tack Free: 6 - 8 hours
Re-coat: After 24 hours

Thinning: No thinning required.

Clean-up: XL Thinner (856X2210), Mineral Spirits or Xylene

Special Note: Product is water and moisture sensitive.

4/06