

**SC 2110 Strontium Chromate Aluminum
(888S2006)**

SC2110 Strontium Chromate Aluminum is a premium blend of resins containing a chromate paste that will provide a tough finish over marginally prepared surfaces. The chromate paste will act as an inhibitor, to prevent corrosion. **SC2110** was developed primarily for tanks and cylinders, but may be used for many other applications.

Technical Data

Type: Modified Oils

Components: One

Colors: Aluminum

Gloss: High

V.O.C: max. 3.85 lbs./gal. or 460 gr/lit
Theoretical unreduced-3.65lbs/gal

Solids by Volume: 45% + or - 2%

Flash Point: In excess of 80° F.

Shelf Life: 1 year

Temperature Resistance:
Up to 500° F. Continuously

Surface Preparation: Remove all contaminants including oil, grease, loose paint, dirt or any other contaminants. Lightly sand surface, or power tool clean.

Application: Brush, roll, or spray

SC2110 Advantages:

- Easy One Coat Coverage
- Can Be Used Without Primer
- Tarnish Resistant
- Holds Brightness
- Long Life

Ordering:

Available in single gallons and five gallon pails

Recommended Primer: Uni-Pox Primer – 855W1370 (Off White) or 855G1368 (Gray-Green).

Mixing: Stir thoroughly prior to, and during use.

Recommended Film Thickness: 1.5 - 2.0 mils dry film.

Spreading Rate: 730 sq. ft per gal. @ 1 mil. 365 - 490 sq. ft. per gal. @ recommended dft.

Pot Life: N/A

Dry Time: @ 77° F.
To Touch: 11/2 - 2 hours
Tack Free: 6 - 8 hours
Re-coat: After 24 hours

Thinning: No thinning required.

Clean-up: XL Thinner (856X2210), Mineral Spirits or Xylene

Special Note: Product is water and moisture sensitive.

04/06