

UNI-POX Primer
(855 Line - 1368, 1370, 1373)

Uni-Pox Primer is a blend of premium resins that are combined with rust inhibitors and other key ingredients, that make this an excellent product. Uni-Pox is offered in 3 colors, and is lead and chrome free. All colors offer excellent weather and corrosion resistance.

Ordering: Available in single gallons and five gallon pails

Technical Data

Type: Premium Blend

Components: One

Colors: 1368 Gray - Green,
1370 Off - White, 1373 Gray

Gloss: Flat

V.O.C: 3.5 - 3.75 lbs. per gallon

Solids by Volume: 50% ± 2%

Flash Point: 58° F.

Shelf Life: 1 year

Temperature Resistance:
200° F. Maximum

Surface Preparation: Surface must be clean and dry. Remove all contaminants including oil, grease, loose paint, dirt or any other contaminants. This product performs well over surfaces cleaned according to SSPC-SP-3 Power Tool Cleaning. In severely corrosive environments, SSPC-SP-6 is recommended.

Uni-Pox Primer can be used for:

- Tanks
- Cylinders
- Ornamental Iron
- Structural Steel
- Aq-Chem Equipment
- Process Equipment
- Plus Many Other Uses

Application: Brush, roll, or spray. Excessive film or surface contamination may cause adhesion problems and solvent entrapment.

Mixing: Stir thoroughly prior use.

Recommended Film Thickness: 2.0 - 2.5 mils dry film.

Spreading Rate: 802 sq. ft per gal. @ 1 mil.
320 – 401 sq. ft. per gal. @ recommended dft.

Pot Life: N/A

Dry Time:

To Touch: 30 minutes
Tack Free: 45 minutes
Re-coat: 2 hours

Thinning: For spray application as necessary with XL Thinner or Xylol, up to 5%. Thinning not normally required for brush or roll application.

Clean-up: XL Thinner or Xylol